

NEW

MINI CENTRIFUGE



5000.EU.01

RPM
4000-7000 RPM

Max. Capacity
2ml x 8

Body Material
ABS

Glassco Laboratory Equipments Pvt. Ltd.

CE
certified



info@glasscolabs.com | www.glasscolabs.com
+91 171 2891633, 6451250

50

years of science

MINI CENTRIFUGE *New*

Product Features

- Patented high tech motor with low working noise
- Low vibration with advanced shock absorbers
- Compact design and can carry higher volume of 2 ml x 8 places
- Easy replacement of rotor
- Maximum relative centrifugal force upto 3260G
- Fast Stopping in 15 seconds with cover breaking time of 3 seconds.
- Spatial rotation for 360° arc shape, low windage resistance with slow temperature increase
- Smooth running of unit with low rotation speed difference.

Included Accessories

Rotor Selection :	5000.303.01	2ml x 8, 0.5ml, 0.2ml adapter each 8 pcs
	5000.303.02	2ml x 8, 8 x 0.2ml tubes strip x 2 rows



Technical Specification :

Body Material	: Main Frame : ABS, Cover : PC, Adapter : PP, Absorber : NBR, Roller : ABS
Speed Range	: 4000-7000 RPM
RCF	: 810~3260xg
Rotor types	: Rotor, 2ml x 8 and 0.2ml x 8, 0.2ml x 8 tubes strip x 2 rows
Max. Capacity	: 2ml x 8
Dimension (WxDxH)	: 174x157x130mm
Speed Control type	: Constant speed
Driving Speed	: Direct drive/vibration
Brake System	: Dynamic
Acceleration Time	: 90% speed in 5 seconds
Deceleration Time	: Cover closed within 15 seconds, cover opens within 6 seconds

Model No.	V	Hz
5000.EU.01	230 V	50