



HEATING MANTLE COMBINED UNIT



2000.EU

Temp
400°C

Mantle Capacity
100 - 500ml

Places
3 & 6

Heating Mantle Material
Glass Fibre Yarn

Glassco Laboratory Equipments Pvt. Ltd.

CE
certified



info@glasscolabs.com | www.glasscolabs.com
+91 171 2891633, 6451250



years of science

HEATING MANTLE COMBINED UNIT

- Aluminium Moulded Construction
- ON-OFF knob for heat power control.
- Stir speed control also available.
- Mantle knitted with glass fibre yarn.
- Heating Mantle Combined unit made of steel
- Provides uniform heating to flasks.
- Heats upto 400°C.
- Stir upto 750 RPM also posible.*
- For Round Bottomed Flasks as per DIN - 12347
- Easy maintenance
- Long Life

Included Accessories:

1. Vertical Rod Stainless Steel length 542 mm,
Ø 9.8 mm (2000.200.01)
 2. Horizontal Rod Stainless Steel length 972 mm,
Ø 9.8 mm (2000.200.02)
 3. Boss Head (2000.200.03)
 4. Clamp (2000.200.04)
- * In select models



OPTIONS FOR
EXTRACTION UNIT WITH
FULL GLASS ASSEMBLY
ALSO AVAILABLE



Technical Specifications :

Heating Mantle Body	: Made of aluminium
Heating Mantle Material	: Glass Fibre Yarn
Mantle Capacity	: To hold standard Round Bottom Flasks upto 500 ml
Temperature Range	: Approx. 400°C
Heating Control	: Electronic power regulator
Stir Control	: Electric regulator
Permissible Ambient Temperature	: 5- 40 °C
Permissible relative moisture	: 80%
IP Class	: 10

Model No. (230VAC 50Hz)	Model No. (230VAC 60Hz)	Mantle Capacity(ml)	Wattage (W)	Fuse Amp.	No. of position of regulator
2000.EU.01	2000.US.01	100 ML	180	1	3/3
2000.EU.02	2000.US.02	250 ML	450	5	3/3
2000.EU.03	2000.US.03	500 ML	600	5	3/3
2000.EU.04	2000.US.04	100 ML	360	1	6/6
2000.EU.05	2000.US.05	250 ML	900	10	6/6
2000.EU.06	2000.US.06	500 ML	1200	10	6/6