

MULTI POSITION STIRRER



410.AG

Temp
120°C

RPM
0-750 RPM

No. of Positions
5

Vessel Capacity
1.25L (Total)

Material
Silicone
& Aluminium

Glassco Laboratory Equipments Pvt. Ltd.

CE
certified



info@glasscolabs.com | www.glasscolabs.com
+91 171 2891633, 6451250

45
years of science



MULTI POSITION STIRRER

- Aluminium Moulded Construction
- Maximum heating plate temperature upto 120°C.
- Maximum stirring speed upto 750 RPM.
- Simultaneously operating stirrers.
- Consistent heating and mixing.
- Silicone surface for anti - skid.
- Narrow foot print for space saving.
- High magnetic strength.
- Knob for electronic variable speed control.
- Knob for regulating variable power.

Technical Specifications

Heating Plate material	: Silicone and Aluminium
Number of stirring positions	: 5
Speed Range	: 0 - 750 RPM
Maximum stirring bar length	: Can use upto 30 mm bar
Temperature range	: Ambient to 120 °C
Temperature constancy in medium	: 2 ±k
Stirring quantity max.	
Vessel Capacity	: 1.25 L Total
Stirring position distance	: 90 mm
Dimension of Hotplate Body	: 554 x 126 x 75 mm
Weight of body	: 3 kgs
Permissible ambient temperature	: 5-40°C
Permissible relative moisture	: 80%
IP Class	: 42

Model No.	V	W	Hz
410.AG.01	230 V	185 W	50
410.AG.02	115 V	185 W	60